




HIGH-SPEED | HIGH-PERFORMANCE ROBOTS - Small to Medium Payloads



RS03N	RS05N	RS05L / RC05L	RS06L	RS10N / RF10N	RS10L	RS15X	RS20N	RS30N / 50N / 80N
Payload: 3 kg	Payload: 5 kg	Payload: 5 kg	Payload: 6 kg	Payload: 10 kg	Payload: 10 kg	Payload: 15 kg	Payload: 20 kg	Payload: 30 kg / 50 kg / 80 kg
Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6
Reach: 620 mm	Reach: 705 mm	Reach: 903 mm	Reach: 1,650 mm	Reach: 1,450 mm	Reach: 1,925 mm	Reach: 3,150 mm	Reach: 1,725 mm	Reach: 2,100 mm
Repeatability: ±0.02 mm	Repeatability: ±0.02 mm	Repeatability: ±0.03 mm	Repeatability: ±0.05 mm	Repeatability: ±0.04 mm	Repeatability: ±0.06 mm	Repeatability: ±0.15 mm	Repeatability: ±0.05 mm	Repeatability: ±0.07 mm



ULTRA HIGH-SPEED PICKING ROBOTS



YF03N	YS02N
Payload: 3 kg	Payload: 2 kg
Axes: 4	Axes: 4
Reach: 1,300 mm	Reach: 600 mm
Repeatability: ±0.1 mm	Repeatability: ±0.04 mm



THE FLEXIBLE HEAVY-DUTY ROBOTS - Large Payloads



ZHE100U	ZXE130U	ZXE130L	ZXE165U	ZXE200S	ZXE300S	ZTE130U / 165U	ZTE165X	ZTE200S
Payload: 100 kg	Payload: 130 kg	Payload: 130 kg	Payload: 165 kg	Payload: 200 kg	Payload: 300 kg	Payload: 130 kg / 165 kg	Payload: 165 kg	Payload: 200 kg
Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6
Reach: 1,634 mm	Reach: 2,651 mm	Reach: 2,951 mm	Reach: 2,651 mm	Reach: 2,651 mm	Reach: 2,501 mm	Reach: 3,230 mm	Reach: 2,830 mm	Reach: 3,230 mm
Repeatability: ±0.3 mm	Repeatability: ±0.3 mm	Repeatability: ±0.3 mm	Repeatability: ±0.3 mm	Repeatability: ±0.3 mm	Repeatability: ±0.3 mm	Repeatability: ±0.3 mm	Repeatability: ±0.3 mm	Repeatability: ±0.3 mm



OPTIMIZED BODY SHOP ROBOTS



BX100N	BX200L
Payload: 100 kg	Payload: 200 kg
Axes: 6	Axes: 6
Reach: 2,200 mm	Reach: 2,597 mm
Repeatability: ±0.2 mm	Repeatability: ±0.2 mm



HIGH WRIST TORQUE ROBOTS - Extra Large Payloads



MXE350L	MXE420L	MXE500N	MXE700N	MTE400N
Payload: 350 kg	Payload: 420 kg	Payload: 500 kg	Payload: 700 kg	Payload: 400 kg
Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6
Reach: 3,018 mm	Reach: 2,778 mm	Reach: 2,540 mm	Reach: 2,540 mm	Reach: 3,503 mm
Repeatability: ±0.5 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm



HIGH-PERFORMANCE PALLETIZING ROBOTS



RD80N	ZDE130S	ZDE250S	MDE400N	MDE500N
Payload: 80 kg	Payload: 130 kg	Payload: 250 kg	Payload: 400 kg	Payload: 500 kg
Axes: 5	Axes: 4	Axes: 4	Axes: 5	Axes: 5
Reach: 2,100 mm	Reach: 3,255 mm	Reach: 3,255 mm	Reach: 3,142 mm	Reach: 3,142 mm
Repeatability: ±0.07 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm




EXPLOSION-PROOF PAINTING ROBOTS



KF121	KG264	KJ264 FLOOR	KJ264 SHELF	KJ264 WALL	KJ314
Payload: 5 kg	Payload: Wrist 20 kg, Arm 30 kg	Payload: Wrist 15 kg, Arm 25 kg	Payload: Wrist 15 kg, Arm 25 kg	Payload: Wrist 15 kg, Arm 25 kg	Payload: Wrist 15 kg, Arm 25 kg
Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 6	Axes: 7
Reach: 1,240 mm	Reach: 2,665 mm	Reach: 2,640 mm	Reach: 2,640 mm	Reach: 2,640 mm	Reach: 3,100 mm
Repeatability: ±0.2 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm	Repeatability: ±0.5 mm



AN EVOLUTION OF ENGINEERING EXCELLENCE



E30/32/33/34	E76/77	E35/37
R / Y / Z / BX / M-SERIES (E30/32/34) - PALLETIZING (E32/33/34) Power: AC200/220/380/415/440/480/515/575 V ±10%, 50/60Hz, 3-Phase, Max. 5 kVA (E30), Max. 10 kVA (E32/33/34)	RS03N (E76) - RS05N, RS05L, RS06L, RS10N (E77) Power: AC200-240V ±10%, 50/60Hz, 1-Phase, Max. 1.5 kVA (E76), Max. 3 kVA (E77)	K-SERIES Power: AC400/440/460/480/515/575V ±10%, 50/60Hz, 3-Phase, Max. 10 kVA (C35), Max. 5 kVA (C37)

Simple & friendly

Note: Clean room robot information available separately.

Kawasaki Robotics (USA), Inc.

United States
28140 Lakeview Drive
Wixom, Michigan 48393
Phone (248) 446-4100

Canada
Phone (905) 304-7784

www.kawasakirobotics.com

Mexico & South America
Phone (52) 33-3110-1895

